

FLAT DECK SCREENS

COAL - AGGREGATES - POTASH ORES - RECYCLING

- Bespoke design to suit customer requirements
- Single Deck
- Twin Deck
- Triple Deck
- High grade boiler steel side plates
- Huck bolt construction
- Exciter unit linear motion
- Over 20 years operational lifespan
- A 'best value' investment



HIGH PERFORMANCE

TOTAL RELIABILITY



LINEAR MOTION FLAT DECK VIBRATING SCREENS

Don Valley Engineering Linear Motion Vibrating Screens, are used around the world in many of the most demanding operations. More than 40 years of experience in vibrating screen design and development has resulted in a standard of screen which is amongst the most robust, reliable and efficient available. Many of our screens have been operational for more than 20 years, and as a result they represent truly exceptional value for investment. We only build machines which last.



SCREEN DATA

Effective Width: Up to 5000mm

Effective Length: Up to

12000mm

Mass: Up to 30T
 Deck Area: Up to 44 M²

Vibratory Motion: Linear

Amplitude: Up to 15mmFrequency / Speed: 850 to 950

cycles/min

Angle of Throw: To suit

application

> Inclination: -5° to +20°

> Flow Speed: 0.3 to 0.5 m/s

Capacity: > 3000 TPH

subject to material

Deck Configurations: Single / Twin /

Triple

Deck Types: Compatible

with most

deck media

GET YOUR FLAT DECK SCREEN SPECIFIED BY THE EXPERTS

Our application engineers will be pleased to provide you with a specification for the best screen to meet your requirements. Simply provide us with the following basic information:-

- Type of material
- Size analysis of feed material
- Bulk Density
- Feed rate (TPH)
- Separation sizes required
- Moisture content



WORLD CLASS PROCESS MACHINERY

Don Valley Engineering Co. Ltd. Sandall Stones Road, Doncaster, DN3 1QR United Kingdom Tel: +44 (0) 1302 881188
Fax: +44 (0) 1302 881000
Email: info@donvalleyeng.com
Web: www.donvalleyeng.com





